

Radio Buttons, Checkboxes & Selects



CODE
HIGHLIGHTS
PROGRAMMING & CODING



Radio Buttons

Radio buttons are used when a user is allowed to select only one option from a list of options.

Radio buttons are created using the `<input>` tag with the `type` attribute set to "radio".

Each radio button in a group should have the same `name` attribute and a unique `value` attribute.

Example:



```
1 <input type="radio" name="gender" value="male"> Male
2 <input type="radio" name="gender" value="female"> Female
```



Checkboxes

Checkboxes are used when a user is allowed to select multiple options from a list of options.

Checkboxes are created using the `<input>` tag with the `type` attribute set to "checkbox".

Each checkbox should have a unique `name` attribute and a `value` attribute.

Example:



```
1 <input type="checkbox" name="fruit" value="apple"> Apple<br>
2 <input type="checkbox" name="fruit" value="banana"> Banana<br>
3 <input type="checkbox" name="fruit" value="orange"> Orange<br>
```

Selects



Select menus are used when a user is allowed to select one option from a dropdown list of options.

Select menus are created using the `<select>` tag, which contains `<option>` tags for each option in the dropdown list.

The selected option is sent to the server when the form is submitted.

Example:



```
1 <select name="color">
2   <option value="red">Red</option>
3   <option value="green">Green</option>
4   <option value="blue">Blue</option>
5 </select>
```